

# SONALIKA

— THE TOUGHEST —  
**PERFORMER**  
« FOR YOUR FIELD »

## 26



RELIABLE MECHANICAL  
TRACTOR

POWER PACKED  
ENGINE

TWIN PROJECTOR  
HEADLAMPS

AGRI, IND. & TURF  
TYRE OPTION

REINFORCED SAFETY  
FEATURES



**COST  
EFFICIENT**  
MECHANICAL TRACTORS

MADE OF  
**REAL  
STEEL**

STRATEGIC  
COLLABORATION  
WITH  
**YANMAR**

**THE TOUGHEST  
PERFORMER  
«FOR YOUR FIELD»**

**S26**

**SONALIKA**



FEATURES	S 26
Model Description	SONALIKA 26
<b>ENGINE</b>	
Engine Type	Mitsubishi 3 Cylinder Engine
HP Category	26
No. of Cylinders	3
Aspiration	Natural
Cubic Capacity (cc)	1318
Rated RPM	2700
Air cleaner	Dry
Cold Start	Standard
Max Torque (nm)	76.3 @ 2700
Exhaust	Underhood Downdraft Silencer
<b>TRANSMISSION</b>	
Drive	4WD
Clutch	Single Clutch
Gearbox	6F+2R
Front Axle	4WD
Transmission	Sliding Mesh
<b>SPEED (FORWARD)</b>	
Maximum Speed (Km/Hr)	14.04 @ 2700
Minimum Speed (Km/Hr)	1.50 @ 2700
<b>BRAKES</b>	
Brakes	Oil Immersed Brakes
Type of actuation	Mechanical
Parking Brake	Independent
<b>DIFFERENTIAL LOCK</b>	
Differential Lock	Yes, Foot Operated
<b>PTO</b>	
PTO (RPM)	540, 1000
PTO (Actuation)	Mechanical
<b>STEERING</b>	
Steering	Power
<b>ELECTRICAL</b>	
Battery	12V, 65Ah
Type of Actuation	12V, 42Amp
Parking Brake	Standard
<b>HYDRAULICS</b>	
3 Point Linkage	Cat-I
Stay Bars	Anchor Chain
Lifting Capacity	600Kg
Auxiliary Hydraulic Circuit	1DA/ 1SA (Optional)
Lift Rods	Standard

FEATURES	S 26
Flow(LPM)	18
<b>SAFETY SWITCH</b>	
Clutch Safety Switch	Standard
PTO Safety Switch	Standard
Neutral Safety Switch	Standard
<b>CAPACITY (LTRS)(+/-5%)</b>	
Fuel Tank (Lit)	26.5
<b>TURNING RADIUS</b>	
Without Brakes (m)	2.3
<b>TYRE</b>	
Front	6.00-12
Rear	8.30-20
<b>DIMENSIONS &amp; WEIGHT(+/-5%)</b>	
Weight (Kg)	960
Wheel Base (mm)	1560
Total Length (mm)	2725
Total Width (mm)	1058
Height (mm) Up to ROPS	2153
Min Ground Clearance (mm)	255
Front Track (mm)	894
Rear Track (mm)	825
<b>OTHERS</b>	
Fuel Indicator Gauge	Standard
Front Tow Hook	Standard
Front & Rear Weights with Std. Ballast	Front weights-15x2
Trailer Hitch	1. Clevis Hitch 2. Swinging Drawbar (Optional)
<b>ROPS</b>	Standard
<b>OPTIONAL FEATURES</b>	
Tyres	<b>TURF TYRES:</b> Front Tyre - 23x8.50-12 Rear Tyre - 33x15.50-16.5  <b>INDUSTRIAL TYRES:</b> Front Tyre- 23x8.50-12 Rear Tyre- 33x15.50-16.5

\*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE, please correlate with latest updates. Accessories shown may not be part of standard product.

**DEALER STAMP**



SONALIKA S26 AF

**INTERNATIONAL TRACTORS LIMITED**

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91 1882 302220, 302221

Fax: +91 1882 302293 | Email: exports@sonalika.com | URL: www.solistractors.com/www.solisworld.com