

SONALIKA

— THE TOUGHEST —
PERFORMER
« FOR YOUR FIELD »

60



AGILE 3 CYLINDER
ENGINE

8F+2R CONSTANT
MESH

HEAVY LIFT
CAPACITY

PARALLELOGRAM
LOADER OPTION

INTEGRATED SAFETY
HVAC CABIN (OPTIONAL)



COST
EFFICIENT
MECHANICAL TRACTORS

MADE OF
REAL
STEEL

STRATEGIC
COLLABORATION
WITH
YANMAR

**THE TOUGHEST
PERFORMER
FOR YOUR FIELD**

S 60

SONALIKA



FEATURES	S 60
Model Description	Sonalika-60
ENGINE	
Engine Type	3100 FLT
HP Category	60
No. of Cylinders	3
Aspiration	Turbo
Cubic Capacity (cc)	2780
Rated RPM	2100
Air cleaner	Dry Type
Cold Start	Standard
Max Torque (Nm)	230Nm@1300erpm
Exhaust	Underhood / Upward
TRANSMISSION	
Drive	4WD
Clutch	Dual Clutch
Gearbox	8F+2R
Front Axle	4WD
Transmission	Constant Mesh
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	33.67
Minimum Speed (Km/Hr)	2.52
BRAKES	
Brakes	Oil Immersed Brake
Type of actuation	Mechanical
Parking Brake	Independent Type
DIFFERENTIAL LOCK	
Differential lock	Standard
PTO	
PTO (rpm)	540
STEERING	
Steering	Power
ELECTRICAL	
Battery	12V, 88Ah
Alternator	12V, 36Amp
Seven pin trailer socket	Standard
HYDRAULICS	
3 point linkage	CAT-II
Stay Bars	Swinging Drawbar
Hydraulic lifting capacity	2000 kg
Auxiliary hydraulic circuit	2DA
Lift rods	Standard

FEATURES	S 60
SAFETY SWITCH	
Clutch Safety Switch	Standard
PTO Safety Switch	Standard
Neutral Safety Switch	Standard
CAPACITY (LTRS)(+/-5%)	
Fuel tank (Lit)	62
TYRE	
Front	9.5-24
Rear	14.9-28
DIMENSION & WEIGHT(+/-5%)	
Weight(kg)	2500
Wheel Base (mm)	2350
Total Length (mm)	3980
Total Width (mm)	1790-1950
Height (mm) Up to ROPS	2650
Min Ground Clearance (mm)	360
Front Track (mm)	1295-1650
Rear Track (mm)	1420-1880
OTHERS	
Fuel Indicator gauge	Standard
Front Tow Hook	Standard, inbuilt in front weight
Front & rear weights with std. Ballast	Base Weight 72Kg+Front 6X31 Kg
Trailer Hitch	Swinging Drawbar
ROPS	Standard
OPTIONAL FEATURES	
Tyres	Rear 9.5X20 / 14.9X28

*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE, Please correlate with latest updates, accessories shown may not be part of standard product.

DEALER STAMP



INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91 1882 302220, 302221

Fax: +91 1882 302293 | Email: exports@sonalika.com | URL: www.sonalika.com/www.solisworld.com