

55" DIGITALFLIP CHART

TE-DP-55



Plug and play



Finger Touch



Pen Touch



Built-in PC Optional



Full HD



Anti-scratch

This Series can be normal interactive LED display, powered by Android based on your requirements.

Full HD resolution guarantee eye-pleasing image quality for ergonomic viewing and versatile digital connectivity optimized to the needs of corporate and signage applications.

With latest advanced LED backlight technology, the display features an amazingly low TCO and maintenance-free operation. Compatible with integrated features like USB media player, speakers and scheduling function, and also qualified for standalone applications in education, commerce, medicine, army etc.

HEADQUARTER: StarBoard Solution Limited: Add: RMS 05-15, 13A/F South Tower, World Finance CTR, Harour City, 17 Canton Rd, TST, KLN Hongkong.

NORTH & SOUTH AMERICAN: StarBoard Solution Inc Add: 2280 Enrico Fermi Dr. Suite#27, San Diego, CA 92154, USA

JAPAN & ASIA: Iboard japan Co.,Ltd Add: 4F Akebono BLD, 5-1-5 Soto-Kanda, Chiyoda-ku TOKYO 101-0021 Japan

EMEA AU NZ SA : StarBoard Solution GmbH Add: Am Borsigturm 53, 13507 Berlin, Germany

Specification

Android System

Android Version	Android 5.1.1
CPU	Quadcore ARM Cortex-A9 1.8 GHz
RAM	2G
ROM	8G
WiFi	√

Display

Screen Type	LED
Screen Size(mm)	1209.6*680.4 mm(54.6inch)
View Angle	178°
Color	8bit, 16.7Million
Resolution	1920*1080
Aspect Ratio	16:9
Brightness	350cd/m ²
Contrast	1200:1
Life Time	30000hrs
Response Time	8ms
Protection Glass	Antiglare Glass
Touch Screen Touch Lifetime	Above 60,000,000 single-dot touch

Power Supply

Voltage Range	AC(100 ~ 240)V-50/60HZ
Rated Power	<150W
Standby Power	<1W

Physical Spec.

Product Dimension W*H*D(mm)	1004.5*598.6*84mm
N.W.(kg)	36.5 kg
CTN Dimension W*H*D(mm)	1400*880*150mm
G.W.(kg)	50.4kg
VESA(mm)	400*400

Software

DrawView X

Touch System

Touch Points	10
Writing mode	Finger, writing pen or any non-transparent object
Technology	Infrared
Accuracy	<2mm
Positioning resolution	32768*32768
Response time	<8ms
Cursor speed	>180dot/s
Communication	Full-speed USB (Plug and Play)
Compatible OS	WINDOWS/LINUX/MAC /Android

Input Port

	2 × USB2.0, 1 × TF Card Slot,
Back Side	1 × LAN(10/100M), 1 × WIFI(2.4G)

Output Port

Back Side	1 × HDMI OUT(MAX support 1080P)
-----------	---------------------------------

Front Button

Back Side	1 × POWER
-----------	-----------

Environment

Operation Temperature	0° C~40°C
Operation Humidity	10% - 90%
Storage Temperature	-20° C~60°C
Storage Humidity	10% - 90%

Accessory

Pen x 2, HDMI Cable(1.8M) x 1, USB Cable(1.5M) x 1,
